

Dryback-Vinyl - 0,7 mm Wear Layer

Format: 187 x 1175 mm

Carton: 3.955 m²

Pallet: 60 cartons - 237.3 m²



Usage Classes



Residential - heavy use



Commercial - very heavy use



Industrial - heavy use

Property

Standard

Value

Adhesive Recommendations



Total Thickness

EN 428
ISO 24346

2,5 mm



AUS GUTEM GRUND

AF 2224
AF 155
AF 180

A2-Zahnleiste



Wear Layer Thickness

EN 429
ISO 24340

0,55 mm



Anspruch verbindet

D 3307
D 3320
D 3330
D 3125



Total Weight

EN 430
ISO 23997

4.551 g / m²



Slip Resistance

EN 13893

R10



Reaction to Fire

EN 13501-1

Bfl s1 on concrete and wood



ECO PRIM T PRO
PLANIPATCH XTRA
ULTRAPLAN BASIC XTRA
ULTRABOND ECO VS60



Chair Castor Suitability

EN 425

No damage



Furniture Leg Test

EN 424

No damage



Impact Sound Reduction

EN 717-2

Δlw = 2db



Underfloor Heating

/

Suitable - bis 27°C



Light Fastness

ISO 105-B02

≤ 6



Dimensional Stability

EN 434
ISO 23999

≤ 0,10 %



Antistatic Properties

EN 1815

≤ 2 kV on concrete



Residual Indentation

EN 433

≤ 0,05 mm



Chemical Resistance

EN 423

High resistance



Electrical Conductivity

EN 1081

≤ 10Ω

Decotec GmbH

Rosemeyerstraße 14
44139 Dortmund
Germany

+49 (0)231/912 900-870

kontakt@decotec-germany.de