

ECO PRIM T PRO – FULL TRANSLATION

APPLICATION AREA

Multi-purpose dispersion primer for use on absorbent and ceramic substrates prior to leveling work.

Also suitable as a primer for absorbent or slightly dusty substrates before applying dispersion, cement or SMP adhesives.

APPLICATION EXAMPLES

- Preparation of cement screeds and concrete substrates with smooth, dense surfaces before applying MAPEI leveling compounds.
- Preparation of surfaces with firmly adhering, moisture-resistant adhesive and leveling compound residues.
- Preparation of substrates such as gypsum/calcium sulfate, wood or OSB panels, terrazzo, ceramic tiles or natural stone.
- Preparation of mastic asphalt screeds according to EN 13813.
- Dust binding on absorbent screeds before installation with MAPEI SMP parquet adhesives.
- Primer between two leveling layers.
- Preparation of porous or dusty substrates before installing LVT coverings.

TECHNICAL CHARACTERISTICS

Eco Prim T Pro is a low-odor, easy-to-apply acrylic dispersion primer with excellent adhesion and water and aging resistance.

It is ready-to-use, light blue, non-flammable and very low emission (EMICODE EC1 Plus).

IMPORTANT NOTES

- For indoor use only.
- Do not use on magnesia or wood-cement screeds.
- Do not use on substrates with rising moisture.

APPLICATION GUIDELINES

Substrate must be dry, solid, clean and free of contaminants.

Apply using roller or brush.

Dilution:

- Cement substrates: up to 1:2
- Calcium sulfate substrates: up to 1:1
- Undiluted on tiles, wood, adhesive residues

Allow to dry completely before applying leveling compounds or adhesives.

CLEANING

Fresh product can be removed with water and soap. Dried material can be removed with alcohol.

CONSUMPTION

50–150 g/m²

PACKAGING

1 kg and 10 kg containers

STORAGE

12 months in original packaging

SAFETY

Ensure ventilation. Avoid contact with eyes and skin.

NOTE

All information is based on current knowledge and does not guarantee product performance in all cases.